



Neocrete: The Best Solution for Concrete Resurfacing



- Concrete is the only sub-base that can typically be renovated or resurfaced without removing the old base and installing a brand-new surface
- Neocrete makes cutting-edge products that can fully do away with this laborious process for other surfaces such as tiles, marble, granite, wood etc by resurfacing without removing
- Neocrete offers the entire range of concrete resurfacing options to metamorphosize your floors

Neocrete's Products

- Polishable or stampable cement systems
- Ready-to-use cement compounds that may be applied at various thickness ranges
- Pre-blended cement mixes that require the addition of sand and water
- Beautiful terrazzo floors

Benefits of Neocrete

- Transform your floors with Neocrete's comprehensive selection of concrete resurfacing solutions
- Eliminate the laborious process of removing the old base and installing a brand-new surface
- Create beautiful, unique designs with Neocrete's cutting-edge products

Neocrete's Services

- Professional installation
- Expert advice and design services
- Customized solutions to fit any surface or style



Neocoat UTM



CONCRETE RESURFACING

EXPERIENCE THE BEAUTY AND DURABILITY OF OUR DECORATIVE FLOORS



Neocoat UTM



Neocoat UTM

Neocoat UTM Microtopping (1-3mm polishable)

Neocoat UTM is a mixture of cement, special additives and polymers that is laid in very thin layers between 1mm and 3mm (in 2 or 3 coats). It is good for resurfacing and provides a decorative, rustic top surface. It also has excellent compressive and tensile strength and may be polished to give an aesthetic, satin-finish surface.

Neocoat UTM can be used on both walls and floors. The beauty and versatility of **Neocoat UTM** go hand and hand. It offers a wide range of hues, textures, and limitless design possibilities; your imagination is the only restriction. A variety of sealers offer protection, ease of maintenance, a range of gloss levels, slip and chemical resistance, as well as numerous other multipurpose functions.

Neoflor 7010 (5-10 mm polishable)

Neoflor 7010 is a 2K polymer modified self-leveling cementitious topping that has excellent strength to withstand moving loads. With unique primers and proprietary application methodology, Neoflor 7010 can be applied over old concrete, new concrete, vitrified tiles, marble or granite floors

- Neoflor 7010 can be self-levelled as well as trowellable and can be used as a stand-alone topping or polished to give smooth and high gloss finish
- It offers good resistance to high impact and abrasion. It provides good surface durability for critical areas of a floor which cannot be closed to traffic easily or economically.
- Neoflor 7010 is suitable for both interior and exterior applications



Neoflor 7010

STAMPABLE NEOFLOR 4010

2-8 mm stampable
floor topping

Neoflor 4010 is a free flowing, self levelling cementitious compound, specially designed for easy application over concrete floors as a stand-alone floor topping or as an underlay for any suitable topping. It be used for repairs and leveling course and may be applied at thickness from 2 to 5 mm. Neoflor 4010 is a one-part system requiring only the addition of water for mixing. It can be optionally supplied with UV resistant colours of limited shades. Neoflor 4010 is also suitable as stampable overlay. Neoflor 4010 is specially designed to be used as levelling cours for parking decks as it achieves very high compressive strength



Neoflor 6010

Neoflor 6010 is a 2K polymeric floor topping, combining graded hard aggregates, cement and resinology additives. The state-of-the-art additives ensures that the product achieves excellent strength within 3 days. This selflevelling topping can be applied over old, worn-out concrete (with suitable primer) or over new concrete directly (wet-on-wet method) to a thickness ranging from 2mm to 5mm. The uniformity in surface level as well as colour achieved with Neoflor 6010 allows this product to be used as an underlay for micro-topping as well. It is suitable for both interior and exterior applications.



Neoflor 4010

NEOFLOR 6010 & NEOFLOR 6010-SC

2-5 mm floor topping or underlay

Neoflor 6010 is a two component polymeric floor topping, and Neoflor 6010-SC is one-component system needing addition of only water. The state-of-the-art additives ensures that both the products achieve excellent strength within 3 days. These self-levelling toppings can be applied over old, worn-out concrete (with suitable primer) or over new concrete directly (wet-on-wet method) to a thickness ranging from 2mm to 5mm. The uniformity in surface level as well as colour achieved with Neoflor 6010 allows it to be used as an underlay for micro-topping as well. It is suitable for both interior and exterior applications.

Application areas include:

- ▶ Retail stores, offices and residences
- ▶ Healthcare centres
- ▶ Concrete resurfacing of industrial floors with light to medium traffic
- ▶ Logistic centres
- ▶ Server rooms, mechanical & utility areas
- ▶ Exterior patios, swimming pool decks and pathways
- ▶ For interior and exterior sports floors



Neoflor 6010

Polyacrylate Cement terrazzo

Cement terrazzo tiles were in vogue for a long time in India. However, cast-in-situ cement terrazzo floorings have got the fancy of designers in order to deliver stunning looks and maintenance-free floors.

Greatest advantages of Neocrete Ultra cement Terrazzo

- Cast-in-situ and hence joint-less and seamless
- Availability of designs and patterns are only limited by the imagination of the architect
- Extremely durable and a typical operating life of cement terrazzo beyond 25 years are not uncommon
- We have developed cement terrazzo flooring materials with new-age polymers to enhance performance by reducing setting times and eliminating shrinkage cracks
- Use of marble chips, glass and other aggregates provide a look and feel which are unachievable in other type of floors
- Our state-of-the-art PU sealer is found to enhance abrasion and stain resistance considerably

Coloured resurfacing

The beauty of coloured cementitious resurfacing is its simplicity as well as universal appeal. Any sub-floor can be converted to a seamless, jointless, polymeric cement flooring that can be pigmented to a broad range of colours to suit the ambience. Patios, swimming pool decks, garden areas, foot-paths or any internal or external areas can be transformed into a work of art. Neocrete offers different products for a variety of thickness options.



Neoflor Ultra cement terrazzo



Neostone D'Corez



NEOSTONE D'COREZ

Neostone D'Corez is a seamless, jointless unique decorative terrazzo flooring for use where no joints or divider strips are required/desired. Neostone D'Corez is made up special cements and additives mixed with a mineral liquid and special aggregates to produce a stunning array of colours and designs that is unmatched in industry.

Exceptional compressive and flexural strength of Neostone D'Corez makes it an ideal flooring solution where hardness, flexibility and wear resistance is required. It also offers fire resistance as well as thermal and acoustic insulation properties



NEOCRETE
UHPC



TRANSFORM YOUR
FLOORS WITH
NEOCRETE'S
COMPREHENSIVE
SELECTION OF
CONCRETE
RESURFACING
SOLUTIONS.



Contact Us

Neocrete technologies Pvt Ltd

Mumbai Office:

817, Hubtown Viva,

Off WEH, Shankarwadi

Jogeshwari (East), Mumbai-400060

Mumbai:022-67416418

email: neocrete@gmail.com

Website: www.neocrete.co.in



CONVERTING THE SPACE
TO A WORK OF ART